

SPECIAL PROCESSING "SP" SERIES HIGH ENDURANCE Valve Springs

High Endurance™ "SP" Springs are wound from "Super Clean" Hi-Tensile Chrome Silicone Wire!

SP
Series



Every Part No. Test-Proven
700
Racing Miles (every batch)

The "SP" series utilizes "Hi-Tensile" Chrome Silicon outer spring material. For applications with radical cams and/or moderately high rpm, where traditional chrome silicon springs prove inadequate, the "SP" series is the next highest level of endurance. All "SP" series springs are Spintron Test-Proven up to 8000 rpm for 700 racing miles.

Part No.	Style	Outer OD/ID	Inner OD/ID	Seat Pressure	Open Pressure	Rate Per Inch	Coil Bind	Max. Net Lift	Type of Cam
8005-SP	Dual w/ Damper	1.530" 1.110"	1.005" .730"	150 lbs @1.875"	435 lbs @1.225"	415	1.160"	.650"	Solid
8205-SP	Dual w/ Damper	1.530" 1.110"	1.005" .730"	150 Lbs @1.900"	440 Lbs @1.300"	480	1.150"	.650"	Solid
9365-SP	Dual w/ Damper	1.550" 1.135"	1.025" .740"	225 Lbs @1.950"	550 Lbs @1.270"	460	1.170"	.680"	Roller

Endurance Plus™ SERIES EXTREME HIGH ENDURANCE Valve Springs

Endurance Plus™ Springs feature a Higher Alloy Outer Spring "Plus" special processing for increased durability!

"PLUS"
Series



Every Part No. Test-Proven
850
Racing Miles (every batch)

The Endurance Plus™ series of valve springs utilizes a specially processed Tool Room Material outer spring for increased endurance/reliability beyond the "SP" series. Endurance Plus™ springs are designed for late models, modifieds, etc., and are Spintron Test-Proven up to 8400 rpm for 850 racing miles.

Part No.	Style	Outer OD/ID	Inner OD/ID	Seat Pressure	Open Pressure	Rate Per Inch	Coil Bind	Max. Net Lift	Type of Cam
8005 PLUS	Dual w/ Damper	1.530" 1.110"	1.005" .730"	140 Lbs @1.875"	400 Lbs @1.275"	420	1.160"	.650"	Solid
8205 PLUS	Dual w/ Damper	1.530" 1.110"	1.005" .730"	150 Lbs @1.900"	420 Lbs @1.300"	440	1.120"	.650"	Solid
9005 PLUS	Dual w/ Damper	1.530" 1.110"	1.005" .725"	170 Lbs @1.900"	455 Lbs @1.300"	455	1.160"	.650"	Solid
9315 PLUS	Dual w/ Damper	1.550" 1.135"	1.025" .740"	220 Lbs @1.900"	530 Lbs @1.240"	480	1.130	.660"	Roller
9365 PLUS	Dual w/ Damper	1.560" 1.145"	1.040" .740"	235 Lbs @1.950"	560 Lbs @1.270"	470	1.170"	.680"	Roller
9375 PLUS	Dual w/ Damper	1.560" 1.145"	1.040" .740"	230 Lbs @1.970"	560 Lbs @1.290"	480	1.190"	.680"	Roller
9375/85 PLUS	Dual w/ Damper	1.560" 1.145"	1.040" .740"	250 Lbs @1.970"	580 Lbs @1.290"	470	1.190"	.680"	Roller
9385 PLUS	Dual w/ Damper	1.560" 1.145"	1.040" .740"	245 Lbs @2.000"	600 Lbs @1.280"	500	1.180"	.720"	Roller